



Safe, simple, and affordable hydrogenation



Safe: No H₂ cylinders and catalyst filtration Powerful: 100 °C and 100 bar capable Fast: results in 4 minutes Simple with built-in video tutorials



A revolutionary bench-top high pressure hydrogenation reactor, uniquely combining continuous-flow microchemistry with endogenous on-demand hydrogen generation and a disposable catalyst cartridge system to create an extremely safe, yet powerful system. It allows fast, safe,

and cost-efficient hydrogenation for both academia, for their education and research purposes, and industry for rapid small scale production with superior yields when compared to conventional methods.



INDUSTRY

- Able to reduce heterocycles to form high fsp³ molecules
- Simple to use with small footprint
- · High pressure lab in your fume hood
- · Fast catalyst and parameter screening
- Selective reaction

ACADEMIA

- High temperature and pressure for new chemistry
- Teach hydrogenation for undergraduates for the first time
- · Simple enough for students to use
- Complete reaction and monitoring in 1 lab session
- Industry accepted technology

Technical Parameters of the H-Cube Mini Plus™	
Temperature range	Ambient to 100 °C
Pressure range	1 bar to 100 bar
Flow Rate	0.1–3 ml/min
Hydrogen Generation	25–30 ml/min
Water Reservoir Capacity	100 ml
Dimensions	Width: 217 mm (8.54") Depth: 290 mm (11.42") Height: 200 mm (7.87") with closed display, 315 mm (12.4") with opened
Weight	7.3 kg (16.09 lb)
Voltage	100-240 V AC
Catalyst Amount	0.1-0.3 g
Concentration	0.01-1M